

## FG236



Issued in accordance with the Construction Products Directive (CPD) 305/2011/EU.  
pgb-Europe nv hereby declares that the products mentioned below comply with the requirements of:

### ETAG 015 – three-dimensional nailing plates

---

1. *Unique identification code of the product-type:*  
**FG236**
2. *Type or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*  
**see annex 1 to this document**
3. *Intended uses of the construction product, in accordance with the applicable harmonized technical specification as foreseen by the manufacturer:*

<b>Generic type:</b>	<i>Angle bracket</i>
<b>Material:</b>	<i>Steel DX51D+Z275</i>
<b>Corrosion protection:</b>	<i>Pre-galvanized</i>
<b>Service class:</b>	<i>Service class I and II</i>
<b>Fire resistance:</b>	<i>NPD</i>
<b>Reaction to fire:</b>	<i>Euroclass A1</i>
<b>Safety in use:</b>	<i>Not relevant</i>
<b>Protection against noise:</b>	<i>Not relevant</i>
<b>Energy, economy and heat retention:</b>	<i>Not relevant</i>
<b>Intended use:</b>	<i>Wood connector as a connection between a beam and a purlin</i>

4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5):*  
**Gutzeit Verbindungssysteme GmbH & Co., Rudolf-Diesel-Strasse 1, D-58730 Fröndenberg, Industriegebiet**
5. *Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2):*  
**NOT RELEVANT**
6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*  
**System 2+**

# DECLARATION OF PERFORMANCE

DoP FG236001B page 2 / 3

7. *In case of the declaration of performance concerning a construction product covered by a harmonized*

**NOT RELEVANT**

8. *In case of the declaration of performance concerning a construction product for which European Technical Assessment has been issued:*

**standard:** ETAG 015  
**certificate:** ETA 09-0133  
**performed by:** Karlsruher Institut für Technologie (KIT)  
**under system:** 2+  
**and issued:** 0769-CPD-6081

9. *Declared performance:*

Essential characteristics	Declared performance	Guideline
Description and dimensions	ETA 09-0133, annex A	ETAG 015
Properties of materials	ETA 09-0133, p 3-8	
Load capacity for characteristic resistances	ETA 09-0133, annex B	ETAG 015

10. *The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of pgb-Europe nv.*

Place and date of issue	Signature
Melle, 09/05/2014	<div style="border: 1px solid black; padding: 2px; display: inline-block;"><b>nv pgb-Europe sa</b> Gontrode Heirweg 170 9090 MELLE BE 0425 888 396</div> Johannes Heye, product manager 

## Annex 1 : Product overview

Steel

[www.pgb-europe.com](http://www.pgb-europe.com)

€

**ASSEMBLY SQUARE** VERSTERKINGSHOEK  
multigaatjes

Material : Steel  
Surface : sendzimir verzinkt  
Type : thickness 2,0 mm

Material : Staal  
Oppervlak : sendzimir verzinkt  
Type : materiaaldikte 2,0 mm


**EQUERRE**  
multi trous

Material : Acier  
Surface : zingué sendzimir  
Type : épaisseur 2,0 mm

**LOCHPLATTENWINKEL**

Material : Stahl  
Oberfläche : sendzimir verzinkt  
Typ : starke 2,0 mm

## FG236 - FG241 Assembly square



Art.Nr	EAN Nr.	Dimensions in mm				Packing Unit
		H	s	W	L	
FG236,020040Z	5410439322461	40	2,00	20,00	40	***** 200
FG236,030030Z	5410439209359	30	2,00	30,00	30	***** 100
FG236,040040Z	5410439322485	40	2,00	40,00	40	***** 100
FG236,040050Z	5410439322508	50	2,00		50	***** 100
FG236,040060Z	5410439322645	60	2,00		60	***** 100
FG236,050050Z	5410439627658	50	2,00	50,00	50	***** 100
FG236,050060Z	5410439322669	60	2,00		60	***** 50
FG236,060060Z	5410439322683	60	2,00	60,00	60	***** 50
FG236,100040Z	5410439686150	40	2,00	100,0	40	***** 10
FG236,140040Z	5410439702164	40	2,00	140,0	40	***** 50
FG236,200040Z	5410439702171	40	2,00	200,0	40	***** 50