

SM1KA001










- *Unieke identificatiecode van het product:*
SMART S-KA, S-KAK
- *Type-, partij- of serienummer, dan wel een ander identificatiemiddel voor het bouwproduct, zoals voorgeschreven in artikel 11, lid 4:*
Zie bijlage 1
- *Beoogde gebruiken van het bouwproduct, overeenkomstig de toepasselijke geharmoniseerde technische specificatie, zoals door de fabrikant bepaald:*

Beoogd gebruik volgens ETAG 001 parts 1 - 2	
Generic type	Torque controlled expansion anchor
Base material	Cracked and non-cracked concrete Reinforced or unreinforced normal weight concrete C20/25 to C50/60 acc. to EN 206-1:2003
Material:	S-KA : Galvanized steel, zinc plated : ISO 4042 A2K $\geq 5\mu\text{m}$ S-KAK: Hot-dip galvanized steel : ISO 10684
Durability	S-KA/ S-KAK : internal dry conditions
Anchorage subject to	Static or quasi-static loads Seismic actions for Performance Category C1 Fire exposure
Fire Resistance	R30-R120
Reaction to fire	A1, in acc. with 96/603/EC
Assumed working life	50 years

- *Naam, geregistreerde handelsnaam of geregistreerd handelsmerk en contactadres van de fabrikant, zoals voorgeschreven in artikel 11, lid 5:*
pgb-Polska sp. z o.o. – Ul. F.W. Redena 3 – 41-807 Zabrze – Polska
- *Het systeem of de systemen voor de beoordeling en verificatie van de prestatiebestendigheid van het bouwproduct, vermeld in bijlage V:*
System 1
- *Indien de prestatieverklaring betrekking heeft op een bouwproduct waarvoor een Europese technische beoordeling is afgegeven:*

ETA - 10/0472 issued by	VTT EXPERT SERVICES OY
Body nr	NB 0809
On the basis of	ETAG 001, part 1 and 2
Under System	1
And issued	09/05/2017

Essentiële kenmerken

STANDARD EMBEDMENT DEPTH							
Installation parameters (ETAG001 part 1 and 2)				M8	M10	M12	M16
	d_o	Nominal diameter of drill bit	[mm]	8	10	12	16
	h_{ef}	Effective standard embedment depth	[mm]	45	60	70	85
	d_f	Fixture clearance hole diameter	[mm]	9	12	14	18
	T_{inst}	Nominal installation torque	[Nm]	20/15 ¹	35	50	120
	h_1	Depth of drilled hole	[mm]	60	75	90	110
	h_{min}	Min. thickness of concrete member	[mm]	100	120	140	170
	s_{min}	Minimum spacing	[mm]	50	50	60	70
	c_{min}	Minimum edge distance	[mm]	50	50	55	85
	Tension load: steel failure						
	$N_{Rk,s}$	Tension steel characteristic resistance	[kN]	13	26	38	69
	γ_{Ms}	Partial safety factor ²	[-]	1,40			
Tension load: concrete cone or splitting failure in concrete							
	$N_{Rk,p}$	Tension characteristic resistance in CRACKED concrete C20/25	[kN]	5	9	12	20
	$N_{Rk,p}$	Tension characteristic resistance in NON-CRACKED concrete C20/25	[kN]	9	16	20	35
	γ_{Mp}	Partial safety factor	[-]	1,80 ³			1,50 ⁴
	ψ_c	Increasing factor C25/30	[-]	1,04			
		Increasing factor C30/37	[-]	1,10			
		Increasing factor C40/50	[-]	1,20			
Increasing factor C50/60		[-]	1,28				
Tension load: concrete cone or splitting failure in concrete							
	$s_{cr,N}$	Critical spacing	[mm]	135	180	210	255
	$s_{cr,sp}$	Critical spacing (splitting)	[mm]	180	240	280	340
	$c_{cr,N}$	Critical edge distance	[mm]	68	90	105	128
	$c_{cr,sp}$	Critical edge distance (splitting)	[mm]	90	120	140	170
	γ_{Mc}	Partial safety factor ²	[-]	1,80 ³			1,50 ⁴
Tension load: displacements							
Cracked and non-cracked concrete C20/25 – C50/60	N	Tension service load	[kN]	2	3,6	4,8	9,5
	δ_{N0}	Displacements under short term tension loads	[mm]	0,3	0,6	0,6	0,7
	$\delta_{N\infty}$	Displacements under long term tension loads	[mm]	1,8	1,6	2,0	1,4
Shear load: steel failure without lever arm							
	$V_{Rk,s}$	Characteristic resistance	[kN]	10	18	23	44
	γ_{Ms}	Partial safety factor ²	[-]	1,25			
	K_2	Factor for considering ductility	[-]	1,00			
Shear load: steel failure with lever arm							
	$M^0_{Rk,s}$	Characteristic resistance	[kN]	21	48	72	186
	γ_{Ms}	Partial safety factor ³	[-]	1,25			
Shear load: concrete pryout failure							
	K	K factor	[-]	1	2		
	γ_{Mpr}	Partial safety factor ²	[-]	1,50			

¹ Installation torque for S-KA is 20Nm and for S-KAK 15Nm

² In absence of other national regulations

³ The installation safety factor of $\gamma_2 = 1,2$ is included


⁴ The installation safety factor of $\gamma_2 = 1,0$ is included

DECLARATION OF PERFORMANCE



DoP SM1KA001 page 3 / 5 – rev02

Installation parameters (ETAG001 part 1 and 2) - continued				M8	M10	M12	M16	
Shear load: concrete edge failure								
	l_f	Effective anchorage depth under shear loads	[mm]	45	60	70	85	
	d_{nom}	Outside anchor diameter	[mm]	8	10	12	16	
	$\psi_{ucr,V}$	CRACKED concrete without edge reinforcement		[-]	1,00			
		CRACKED concrete with straight edge reinforcement > ϕ 12mm			1,20			
		CRACKED concrete with edge reinforcement and closely spaced stirrups ($a \leq 100$ mm) or non-cracked concrete			1,40			
γ_{Mc}	Partial safety factor ²	[-]	1,50					
Shear load: displacements								
<i>Cracked and non-cracked concrete C20/25 – C50/60</i>	V	Service shear load	[kN]	5,7	10,3	13,1	25,1	
	δ_{V0}	Short term displacement under shear loads	[mm]	1,7	1,7	2,4	3,2	
	$\delta_{V\infty}$	Long term displacement under shear loads	[mm]	2,6	2,6	3,6	4,8	

Characteristic tension resistance in cracked and non-cracked concrete C20/25 to C50/60 under fire exposure 																	
SMART THROUGH BOLT		M8				M10				M12				M16			
Fire resistance duration	R.... [min]	30	60	90	120	30	60	90	120	30	60	90	120	30	60	90	120
Steel failure																	
Characteristic resistance	$N_{RK,s,fi}$ [kN]	1,3	0,7	0,4	0,3	2,3	1,3	0,8	0,5	3,6	2,0	1,3	0,9	5,3	3,0	1,8	1,3
Pull-out failure																	
Characteristic resistance	$N_{RK,p,fi}$ [kN]	1,3		1,0		2,3		1,8		3,0		2,4		5,0		4,0	
Concrete cone failure																	
Characteristic resistance	$N^0_{RK,p,fi}$ [kN]	2,4		2,0		5,0		4,0		7,4		5,9		12,0		9,6	
Spacing	$S_{cr,N}$ [mm]	4 x h_{ef}															
	S_{min} [mm]	50				55				60				70			
Edge distance	$C_{cr,N}$ [mm]	2 x h_{ef}															
	C_{min} [mm]	Fire attack from one side:				$C_{min} = 2xh_{ef}$				Fire attack from more than one side:				$C_{min} \geq 300$ mm			

In absence of other national regulations the partial safety factor for resistance under fire exposure $\gamma_{M,fi} = 1,0$ is recommended.



DECLARATION OF PERFORMANCE



DoP SM1KA001 page 4 / 5 – rev02

Characteristic shear resistance in cracked and non-cracked concrete C20/25 to C50/60 under fire exposure																	
SMART THROUGH BOLT		M8				M10				M12				M16			
Fire resistance duration	R... [min]	30	60	90	120	30	60	90	120	30	60	90	120	30	60	90	120
Steel failure without lever arm																	
Characteristic resistance	$V_{Rk,s,fi}$ [kN]	1,3	0,7	0,4	0,3	2,3	1,3	0,8	0,5	3,6	2,0	1,3	0,9	5,3	3,0	1,8	1,3
Steel failure with lever arm																	
Characteristic resistance	$M^0_{Rk,s,fi}$ [Nm]	1,8	1,3	0,8	0,6	3,6	2,6	1,6	1,1	6,4	4,6	2,8	1,9	16,2	11,7	7,2	4,9
Concrete pryout failure																	
K factor	K [-]	1,0				2,0				2,0				2,0			
Characteristic resistance	$V^0_{Rk,cp,fi}$ [kN]	2,4		2,0		10,0		8,0		14,8		11,8		24,0		19,2	
Concrete edge failure																	
The initial value $V^0_{Rk,c,fi}$ of the characteristic resistance in concrete C20/25 to C50/60 under fire exposure may be determined by: $V^0_{Rk,c,fi} = 0,25 \times V^0_{Rk,c}$ ($\leq R90$) $V^0_{Rk,c,fi} = 0,20 \times V^0_{Rk,c}$ (R120) With $V^0_{Rk,c}$ initial value of the characteristic resistance in cracked concrete C20/25 under normal temperature.																	
In absence of other national regulations the partial safety factor for resistance under fire exposure $\gamma_{M,fi} = 1,0$ is recommended.																	



Characteristic values for seismic category C1 (EOTA TR 045)							
SMART S-KA, S-KAK			M8	M10	M12	M16	
Steel failure for tension load							
$N_{Rk,s,seis}$	Characteristic resistance	[kN]	13	26	38	69	
$\gamma_{Ms,seis}$	Partial safety factor	[-]	1,40				
Pull-out failure							
$N_{Rk,p,seis}$	Characteristic tension load in cracked concrete C20/25	[kN]	5	9	12	20	
$\gamma_{Mp,seis}$	Partial safety factor	[-]	1,80				1,50
Concrete cone failure (see TR 045)							
h_{ef}	Effective anchorage depth	[mm]	45	60	70	85	
$\gamma_{Mc,seis}$ $\gamma_{Msp,seis}$	Partial safety factor	[-]	1,80				1,50
Steel failure for without lever arm							
$V_{Rk,s,seis}$	Characteristic resistance	[kN]	5,6	11,9	15,4	31,2	
$\gamma_{Ms,seis}$	Partial safety factor	[-]	1,25				
Concrete edge failure (see TR 045)							
$l_f = h_{ef}$	Effective anchor length	[mm]	45	60	70	85	
d_{nom}	Outside anchor diameter	[mm]	1,50				



- De prestaties van het in de punten 1 en 2 omschreven product zijn conform de in punt 9 aangegeven prestaties. Deze prestatieverklaring wordt verstrekt onder de exclusieve verantwoordelijkheid van de in punt 4 vermelde fabrikant:

Plaats en datum van uitgave	Ondertekend voor en namens de fabrikant door
Melle, 09/05/2017	nv pgb-Europe sa Gontrode Heirweg 170 9090 MELLE BE 0425 888 396 Johannes Heye, product manager 



Annex 1 : Product overview

S-KA (wit verzinkt)

SM1KA/08072 Z	SM1KA/12118 Z
SM1KA/08092 Z	SM1KA/12128 Z
SM1KA/08112 Z	SM1KA/12148 Z
SM1KA/08147 Z	SM1KA/12163 Z
SM1KA/10092 Z	SM1KA/12178 Z
SM1KA/10102 Z	SM1KA/12200 Z
SM1KA/10112 Z	SM1KA/16123 Z
SM1KA/10132 Z	SM1KA/16138 Z
SM1KA/10162 Z	SM1KA/16168 Z
SM1KA/12103 Z	SM1KA/16178 Z
SM1KA/12108 Z	

S-KAK (vuurverzinkt)

SM1KA/08072 VZ	SM1KA/12118 VZ
SM1KA/08092 VZ	SM1KA/12128 VZ
SM1KA/08112 VZ	SM1KA/12148 VZ
SM1KA/08147 VZ	SM1KA/12163 VZ
SM1KA/10092 VZ	SM1KA/12178 VZ
SM1KA/10102 VZ	SM1KA/12200 VZ
SM1KA/10112 VZ	SM1KA/16123 VZ
SM1KA/10132 VZ	SM1KA/16138 VZ
SM1KA/10162 VZ	SM1KA/16168 VZ
SM1KA/12103 VZ	SM1KA/16178 VZ
SM1KA/12108 VZ	